2009 Tacoma Product Reference
Specifications / Dimensions / Weights & Capacities

Revision 1 - Issue Date: 13 Mar 08

	Regular Cab (B-Cab)				Access Cab (C-Cab)									Double Cab (D-Cab)				
	4x2		PreRunner	4x4	4x2		X-Runner	PreRunner			4x4			PreRunner	PreR L/B	4x4		4x4 LB
	4 cyl	4 cyl	4 cyl	4 cyl	4 cyl	4 cyl	V6	4 cyl	V6	V6	4 cyl	V6	V6	V6	V6	V6	V6	V6
	5MT	4AT	5MT	5MT	5MT	4AT	6MT	5MT	6MT	5AT	5MT	6MT	5AT	5AT	5AT	6MT	5AT	5AT
	TRN220L TRMDKA	TRN220L TRPDKA	TRN260L TRMDKA	TRN240L TRMDKA	TRN225L CRMDKA	TRN225L CRPDKA	GRN225L CRFDKA	TRN265L CRMDKA	GRN265L CRFDKA	GRN265L CRADKA	TRN245L CRMDKA	GRN245L CRFDKA	GRN245L CRADKA	GRN265L PRADKA	GRN270L PRADKA	GRN245L PRFDKA	GRN245L PRADKA	GRN250L PRADKA
	7103	7104	7131	7503	7113	7114	7153	7161	7163	7164	7513	7553	7554	7188	7190	7593	7594	7596
Specification / Dimension	$15,170	$16,070	$16,055	$19,130	$19,205	$20,105	$25,285	$19,965	$21,420	$22,300	$23,040	$24,595	$25,475	$23,500	$25,695	$26,575	$24,000	$27,075
Engine																		
Type	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE	1GR-FE	2TR-FE	1GR-FE	1GR-FE	2TR-FE	1GR-FE	1GR-FE	1GR-FE	1GR-FE	1GR-FE	1GR-FE	1GR-FE
Displacement (cc)	2964	2964	2964	2964	2964	2964	3956	2964	3956	3956	2964	3956	3956	3956	3956	3956	3956	3956
Valve mechanism	16V DOHC w/VVTi	16V DOHC w/VVTi	16V DOHC w/VVTi	16V DOHC w/VVTi	16V DOHC w/VVTi	16V DOHC w/VVTi	24V DOHC w/VVTi	16V DOHC w/VVTi	24V DOHC w/VVTi	24V DOHC w/VVTi	16V DOHC w/VVTi	24V DOHC w/VVTi	24V DOHC w/VVTi	24V DOHC w/VVTi	24V DOHC w/VVTi	24V DOHC w/VVTi	24V DOHC w/VVTi	24V DOHC w/VVTi
Bore x stroke (mm)	95.0 x 95.0	95.0 x 95.0	95.0 x 95.0	95.0 x 95.0	95.0 x 95.0	95.0 x 95.0	94.0 x 95.0	95.0 x 95.0	94.0 x 95.0	94.0 x 95.0	95.0 x 95.0	94.0 x 95.0	94.0 x 95.0	94.0 x 95.0	94.0 x 95.0	94.0 x 95.0	94.0 x 95.0	94.0 x 95.0
Compression ratio	9.6:1	9.6:1	9.6:1	9.6:1	9.6:1	9.6:1	10.0:1	9.6:1	10.0:1	10.0:1	9.6:1	10.0:1	10.0:1	10.0:1	10.0:1	10.0:1	10.0:1	10.0:1
HP @ rpm	159 @5200	159 @5200	159 @5200	159 @5200	159 @5200	159 @5200	236 @ 5200	159 @5200	236 @ 5200	236 @ 5200	159 @5200	236 @ 5200	236 @ 5200	236 @ 5200	236 @ 5200	236 @ 5200	236 @ 5200	236 @ 5200
Torque (lb-ft) @ rpm	280 @ 3800	280 @ 3800	280 @ 3800	280 @ 3800	280 @ 3800	280 @ 3800	266 @4000	280 @ 3800	266 @4000	266 @4000	280 @ 3800	266 @4000	266 @4000	266 @4000	266 @4000	266 @4000	266 @4000	266 @4000
Transmission																		
Type	R155	A340E	R155	R155F	R155	A340E	RA60	R155	RA60	A750E	R155F	RA60F	A750F	A750E	A750E	RA60F	A750F	A750F
1st gear	3.954	2.804	3.954	3.954	3.954	2.804	4.171	3.954	4.171	3.520	3.954	4.171	3.520	3.520	3.520	4.171	3.520	3.520
2nd gear	2.062	1.531	2.062	2.062	2.062	1.531	2.190	2.062	2.190	2.042	2.062	2.190	2.042	2.042	2.042	2.190	2.042	2.042
3rd gear	1.436	1.000	1.436	1.436	1.436	1.000	1.488	1.436	1.488	1.400	1.436	1.488	1.400	1.400	1.400	1.488	1.400	1.400
4th gear	1.000	0.705	1.000	1.000	1.000	0.705	1.193	1.000	1.193	1.000	1.000	1.193	1.000	1.000	1.000	1.193	1.000	1.000
5th gear	0.805	-	0.805	0.805	0.805	-	1.000	0.805	1.000	0.716	0.805	1.000	0.716	0.716	0.716	1.000	0.716	0.716
6th gear	-	-	-	-	-	-	0.849	-	0.849	-	-	0.849	-	-	-	0.849	-	-
Reverse	4.220	2.393	4.220	4.220	4.220	2.393	3.607	4.220	3.607	3.224	4.220	3.607	3.224	3.224	3.224	3.607	3.224	3.224
Rear axle ratio	3.307	3.583	4.100	4.100	3.307	3.583	3.153	4.100	3.727	3.727	4.100	3.727	3.727	3.727	3.727	3.727	3.727	3.727
Transfer case ratio, high (4x4 models)	–	–	–	1.00	–	–	–	–	–	–	1	1	1	–	–	1	1	1
Transfer case ratio, low (4x4 models)	–	–	–	2.57	–	–	–	–	–	–	2.57	2.57	2.57	–	–	2.57	2.57	2.57
Fuel Economy																		
City	20	19	20	17	20	19	15	20	15	17	17	14	16	17	17	14	16	16
Highway	26	25	26	22	26	25	19	26	19	21	22	19	20	21	21	19	20	20
Combined	22	21	22	19	22	21	17	22	17	18	19	16	18	18	18	16	18	18
Fuel Cost (15k mi / $2.80 per gallon)	$1,911	$1,999	$1,911	$2,209	$1,911	$1,999	$2,470	$1,911	$2,470	$2,335	$2,209	$2,625	$2,335	$2,335	$2,335	$2,625	$2,335	$2,335
Maneuverability																		
Turning circle diameter (curb-to-curb, in feet)	18.4	18.4	18	18	21	21	21	20.3	20.3	20.3	20.3	20.3	20.3	20.3	22	20.3	20.3	22
Steering wheel turns, lock-to-lock	3.43	3.43	3.64	3.64	3.43	3.43	3.43	3.64	3.64	3.64	3.64	3.64	3.64	3.64	3.64	3.64	3.64	3.64
Off-Highway																		
Approach angle (degrees)	27	27	35	35	27	27	19	35	35	35	35	35	35	35	35	35	35	35
Departure angle (degrees)	20	20	26	26	20	20	19	26	26	26	26	26	26	26	25	26	26	25
Ramp breakover angle (degrees)	21	21	27	27	20	20	15	21	21	21	21	21	21	21	20	21	21	20
Minimum running ground clearance (inches)	8.1	8.1	9.3	9.3	8.1	8.1	8.1	9.3	9.3	9.3	9.3	9.3	9.3	9.3	9.3	9.3	9.3	9.3
Exterior Dimensions (inches)																		
Overall height	65.8	65.8	69.9	69.9	66.1	66.1	65.6	71.3	71.3	71.3	71.3	71.3	71.3	70.1	70.1	70.1	70.1	70.1
Overall width	72.2	72.2	74.6	74.6	72.2	72.2	74	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6	74.6
Overall length	190.4	190.4	190.4	190.4	208.1	208.1	208.1	208.1	208.1	208.1	208.1	208.1	208.1	208.1	221.3	208.1	208.1	221.3
Wheelbase	109.6	109.6	109.6	109.6	127.4	127.4	127.4	127.4	127.4	127.4	127.4	127.4	127.4	127.4	140.6	127.4	127.4	140.6
Bed length	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	73.5	60.3	73.5	60.3	60.3	73.5
Bed height	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0	18.0
Bed width, total	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4	53.4
Bed width, between wheelwells	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5	41.5
Track, front	61.0	61.0	63.0	63.0	61.0	61.0	62.2	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0
Track, rear	61.0	61.0	63.4	63.4	61.0	61.0	62.2	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4	63.4
Interior Dimensions, Front (inches)																		
Head room	40.0	40.0	40.0	40.0	40	40	40	40	40	40	40	40	40	40.2	40.2	40.2	40.2	40.2
Hip room	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6
Leg room	41.3	41.3	41.3	41.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Shoulder room	58.1	58.1	58.1	58.1	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7
Interior passenger volume (cu. ft.)	56.1	56.1	56.1	56.1	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.6	55.8	55.8	55.8	55.8	55.8
Interior Dimensions, Rear (inches)																		
Head room	-	-	-	-	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2	35.2
Hip room	-	-	-	-	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	53.6	55.2	55.2	55.2	55.2	55.2
Leg room	-	-	-	-	28.1	28.1	28.1	28.1	28.1	28.1	28.1	28.1	28.1	28.1	28.1	28.1	28.1	28.1
Shoulder room	-	-	-	-	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	57.7	59.3	59.3	59.3	59.3	59.3
Interior passenger volume (cu. ft.)	-	-	-	-	33.1	33.1	33.1	33.1	33.1	33.1	33.1	33.1	33.1	43.1	43.1	43.1	43.1	43.1
Maximum seating capacity	3	3	3	3	4	4	4	4	4	4	4	4	4	5	5	5	5	5
Weights and Capacities (pounds)																		
Gross Vehicle Weight Rating (GVWR)	4,600	4,650	5,000	5,100	4,900	4,900	4,700	5,250	5,250	5,250	5,350	5,350	5,350	5,350	5,350	5,450	5,450	5,450
Curb weight	3,250	3,270	3,430	3,665	3,560	3,580	3,805	3,720	3,810	3,835	3,955	4,045	4,070	3,920	3,975	4,130	4,155	4,190
Payload	1,350	1,380	1,570	1,435	1,340	1,320	895	1,530	1,440	1,415	1,395	1,305	1,280	1,430	1,375	1,320	1,295	1,260
Gross Combined Weight Rating (GCWR)	7,500	7,500	8,000	8,000	7,500	7,500	na	8,000	8,100	8,100	8,000	8,100	8,100	8,100	8,100	8,100	8,100	8,100
Gross Combined Weight Rating (GCWR) w/V6 Tow P	-	-	-	-	-	-	-	-	11,100	11,100	-	11,100	11,100	11,100	11,100	11,100	11,100	11,100
Towing capacity, standard	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500
Towing capacity, maximum (w/V6 Tow Pkg)	-	-	-	-	-	-	-	-	6,500	6,500	-	6,500	6,500	6,500	6,500	6,500	6,500	6,500
Tongue load, standard	350	350	350	350	350	350	350	350	350	350	350	350	350	350	350	350	350	350
Tongue load, maximum (w/V6 Tow Pkg)	-	-	-	-	-	-	-	-	650	650	-	650	650	650	650	650	650	650

NOTE: All pricing information listed above is unofficial. Please refer to the 2009 Price Guide for official pricing information.